

Fiche Technique Compresseur d'air sans huile de volute



Photo non contractuelle

| Modèle | La pression maximal | | Capacité (FAD)* | | | | Puissance du moteur | | Nombre de l'élément de vis Units | Le tube d'échappement inch | Niveau de bruit** dB(A) | Dimension (mm) | | | Poids kg |
|--------|---------------------|------|-----------------|----|-------|----|---------------------|-----|-------------------------------------|-------------------------------|----------------------------|----------------|-----|------|-------------|
| | bar(g) | psig | 50 Hz | | 60 Hz | | kW | hp | | | | L | W | H | |
| DWW-2 | 7.0 | 102 | 0.25 | 9 | 0.24 | 8 | 2.2 | 3 | 1 | Rc1/2" | 65 | 920 | 720 | 940 | 230 |
| | 8.0 | 116 | 0.24 | 9 | 0.23 | 8 | 2.2 | 3 | | Rc1/2" | 65 | 920 | 720 | 940 | 230 |
| | 10.0 | 145 | 0.22 | 8 | 0.21 | 7 | 2.2 | 3 | | Rc1/2" | 65 | 920 | 720 | 940 | 230 |
| DWW-3 | 7.0 | 102 | 0.40 | 14 | 0.43 | 15 | 3.7 | 5 | 1 | Rc1/2" | 65 | 920 | 720 | 940 | 230 |
| | 8.0 | 116 | 0.39 | 14 | 0.40 | 14 | 3.7 | 5 | | Rc1/2" | 65 | 920 | 720 | 940 | 230 |
| | 10.0 | 145 | 0.37 | 13 | 0.37 | 13 | 3.7 | 5 | | Rc1/2" | 65 | 920 | 720 | 940 | 230 |
| DWW-5 | 7.0 | 102 | 0.51 | 18 | 0.47 | 16 | 5.5 | 7.5 | 2 | Rc1" | 68 | 1150 | 760 | 1020 | 360 |
| | 8.0 | 116 | 0.48 | 17 | 0.46 | 16 | 5.5 | 7.5 | | Rc1" | 68 | 1150 | 760 | 1020 | 360 |
| | 10.0 | 145 | 0.44 | 16 | 0.42 | 15 | 5.5 | 7.5 | | Rc1" | 68 | 1150 | 760 | 1020 | 360 |
| DWW-7 | 7.0 | 102 | 0.80 | 28 | 0.86 | 30 | 7.5 | 10 | 2 | Rc1" | 68 | 1150 | 760 | 1020 | 360 |
| | 8.0 | 116 | 0.78 | 28 | 0.80 | 28 | 7.5 | 10 | | Rc1" | 68 | 1150 | 760 | 1020 | 360 |
| | 10.0 | 145 | 0.74 | 26 | 0.74 | 26 | 7.5 | 10 | | Rc1" | 68 | 1150 | 760 | 1020 | 360 |
| DWW-11 | 7.0 | 102 | 1.20 | 42 | 1.26 | 44 | 11 | 15 | 3 | Rc1" | 70 | 1150 | 760 | 1400 | 500 |
| | 8.0 | 116 | 1.17 | 41 | 1.20 | 42 | 11 | 15 | | Rc1" | 70 | 1150 | 760 | 1400 | 500 |
| | 10.0 | 145 | 1.11 | 39 | 1.10 | 39 | 11 | 15 | | Rc1" | 70 | 1150 | 760 | 1400 | 500 |

| | | | | | | | | | | | | | | | |
|---------------|------|-----|------|-----|------|-----|----|----|----|----------|----|------|------|------|------|
| DWW-15 | 7.0 | 102 | 1.60 | 56 | 1.73 | 61 | 15 | 20 | 4 | Rc1" | 70 | 1800 | 1300 | 1440 | 800 |
| | 8.0 | 116 | 1.56 | 55 | 1.61 | 57 | 15 | 20 | | Rc1" | 70 | 1800 | 1300 | 1440 | 800 |
| | 10.0 | 145 | 1.47 | 52 | 1.47 | 52 | 15 | 20 | | Rc1" | 70 | 1800 | 1300 | 1440 | 800 |
| DWW-18 | 7.0 | 102 | 2.00 | 71 | 2.07 | 73 | 18 | 25 | 5 | Rc1" | 72 | 1930 | 1270 | 1340 | 860 |
| | 8.0 | 116 | 1.95 | 69 | 1.97 | 70 | 18 | 25 | | Rc1" | 72 | 1930 | 1270 | 1340 | 860 |
| | 10.0 | 145 | 1.84 | 65 | 1.81 | 64 | 18 | 25 | | Rc1" | 72 | 1930 | 1270 | 1340 | 860 |
| DWW-22 | 7.0 | 102 | 2.40 | 85 | 2.53 | 89 | 22 | 30 | 6 | Rc1" | 72 | 1930 | 1270 | 1340 | 900 |
| | 8.0 | 116 | 2.34 | 83 | 2.41 | 85 | 22 | 30 | | Rc1" | 72 | 1930 | 1270 | 1340 | 900 |
| | 10.0 | 145 | 2.21 | 78 | 2.21 | 78 | 22 | 30 | | Rc1" | 72 | 1930 | 1270 | 1340 | 900 |
| DWW-30 | 7.0 | 102 | 3.20 | 113 | 3.44 | 121 | 30 | 40 | 8 | Rc1-1/4" | 75 | 2030 | 1260 | 1720 | 1200 |
| | 8.0 | 116 | 3.12 | 110 | 3.28 | 116 | 30 | 40 | | Rc1-1/4" | 75 | 2030 | 1260 | 1720 | 1200 |
| | 10.0 | 145 | 2.95 | 104 | 3.01 | 106 | 30 | 40 | | Rc1-1/4" | 75 | 2030 | 1260 | 1720 | 1200 |
| DWW-37 | 7.0 | 102 | 4.00 | 141 | 4.25 | 150 | 37 | 50 | 10 | Rc1-1/2" | 75 | 2030 | 1260 | 2100 | 1420 |
| | 8.0 | 116 | 3.89 | 138 | 4.05 | 143 | 37 | 50 | | Rc1-1/2" | 75 | 2030 | 1260 | 2100 | 1420 |
| | 10.0 | 145 | 3.68 | 130 | 3.72 | 131 | 37 | 50 | | Rc1-1/2" | 75 | 2030 | 1260 | 2100 | 1420 |

*) Débit d'air se conforme à la norme ISO 1217 : 2009, Annexe C: Pression d'admission absolue 1 bar (a), température de refroidissement et d'admission 20 ° C

**) Niveau de bruit est en accord avec la norme ISO 2151 et la norme de base ISO 9614-2, fonctionnement à la pression de fonctionnement maximale et à la vitesse maximale; tolérance: ± 3 dB (A)